



## Torch neck

Item number	Usable for	Bending angle (°)	Suitable for wire diameter (mm)	L1 (mm)
52000	ME185A, ME200A	45	0.6 - 1.4	65.0
53000	ME300A	45	0.6 - 1.4	92.0
53530	MER300ASC	180	0.8 - 1.4	207.5
53540	MER300ASC	45	0.8 - 1.4	171.0
53550	MER300ASC	22.5	0.8 - 1.4	198.5
53026	ME303AF	40	0.6 - 1.6	92.0
53300	ME352WSC	45	0.8 - 2.0	139.0
53301	ME352WSC	60	0.8 - 2.0	138.0
53500	MER352WSC	180	0.8 - 2.0	207.5
53510	MER352WSC	45	0.8 - 2.0	171.0
53520	MER352WSC	22.5	0.8 - 2.0	198.5
53711	ME357A	flexible	0.6 - 1.6	140.0
117801	ME357A	flexible	0.6 - 1.6	160.0
53702	ME357A	45	0.6 - 1.6	113.0
54056	ME395A	45	0.8 - 2.0	127.0
54137	ME397A	45	0.8 - 2.0	118.0
54138	ME397A	60	0.8 - 2.0	117.0
54134	ME397A	80	0.8 - 2.0	98.0
54017	ME400A	45	0.8 - 2.0	127.0
54530	MER400ASC	180	0.8 - 2.0	205.5
54540	MER400ASC	45	0.8 - 2.0	169.5
54550	MER400ASC	22.5	0.8 - 2.0	197.0
54100	ME400W	45	0.8 - 2.4	112.0
54027	ME403AF	40	0.8 - 2.4	127.0
54400	ME452WSC	45	0.8 - 2.4	140.0
54401	ME452WSC	60	0.8 - 2.4	139.0
54440	MER452WSC	180	0.8 - 2.4	207.5
54450	MER452WSC	45	0.8 - 2.4	171.0
54460	MER452WSC	22.5	0.8 - 2.4	198.5
55020	ME500A	45	0.8 - 2.4	144.0
117532	ME500A	45	0.8 - 2.4	278.0
55069	ME503WF	40	0.8 - 3.2	130.0
55060	ME500W	40	0.8 - 3.2	130.0
55530	MER500ASC	180	0.8 - 2.4	206.0
55540	MER500ASC	45	0.8 - 2.4	170.0
55550	MER500ASC	22.5	0.8 - 2.4	197.5
55180	ME552WSC	45	0.8 - 2.8	141.0
117550	ME552WSC	45	0.8 - 2.8	277.0
55185	ME552WSC	60	0.8 - 2.8	140.0
55600	MER552WSC	180	0.8 - 2.8	207.5
55610	MER552WSC	45	0.8 - 2.8	171.0

Item number	Usable for	Bending angle (°)	Suitable for wire diameter (mm)	L1 (mm)
55620	MER552WSC	22.5	0.8 - 2.8	198.5
117407	ME652WSC	45	0.8 - 2.4	146.0
100257	MER652WSC	180	0.8 - 3.2	234.5
100258	MER652WSC	45	0.8 - 3.2	190.0
100259	MER652WSC	22.5	0.8 - 3.2	223.5
117583	MER652WSC	20	0.8 - 3.2	227.7